



HITCHINER

Since 1946

**THE LEADING PROVIDER OF INNOVATIVE TECHNOLOGY
SOLUTIONS FOR INVESTMENT CASTINGS**

Counter gravity investment casting for fuel pressurized GDI applications

14 June 2012- 10:50AM






Hitchiner profile

- Established in 1946 , core business investment casting
- 1975 first patent for counter gravity Investment casting technology.
- \$190M Sales (2011), 50% automotive, 50% aerospace
- 1,800 employees worldwide
- Operations in US and Mexico serving markets of North America, Europe and Asia
 - 5 primary manufacturing plants
 - Combined 1 million square feet of manufacturing space




Investment Casting Process






Process stage 1: Wax

Conventional



Wax injection

Multiple patterns
injected in a ring



Cutoff plane

Wax assembly

Stacking of rings


Hitchiner





Process stage 2: shell

Conventional



Shell building

Robot processes
multiple molds

Hitchiner



Dewax



Autoclave with
Wax recycle





Process stage 3: metal casting

Conventional



Casting

Countergravity

Ceramic removal

Automated blasting
On separated castings


Hitchiner





Process stage 4: finishing

Conventional



Cutoff planes



Cutoff from mold



Finishing/machining


Hitchiner

Not required, parts are
Not attached to each other





Counter Gravity Casting



Growing through Excellence



Supported Shell Counter-gravity Low pressure
Air melt casting





Quality Advantages by a Controlled Process


- **Cylindrical Symmetry arrangement of parts around a center sprue**
 - **Solidification control**
 - Uniform thermal gradients lead to good feeding and directional solidification
- **The molten metal is cast into the mold directly from the melting furnace**
 - **Excellent metal cleanliness**
 - Metal is drawn through a snout that enters the melt through clean metal.
 - In gravity pouring, the slag on the metal floats across the surface of the melt and can be poured into the mold creating inclusions
 - **Precise temperature control**
 - Furnace power can be adjusted to maintain constant metal temperature from mold to mold
 - In gravity pouring from a ladle, the metal temperature is rapidly dropping. The metal temperature of the first mold cast from the ladle will be a different than the second
 - **Metal filling is controlled by the vacuum system compared to gravity pouring.**
 - Controlled rate of vacuum application for consistent and controlled mold filling
 - Thin walls and very fine details can be cast
- **High density sprue loading**
 - Central column not solidified returns to melt: castings are not attached when solid
 - High shell and foundry throughput for high volume part applications



High sprue loading

Central feeding
column not solidified

No need to space
Parts for gate cut off





Higher metal utilization



Feeding column not solidified (50% of total molten alloy)



Metallurgical cleanliness



85 % less inclusions in a CLA casting



GDI Fuel Rail injector Cups



Growing through Excellence




GDI Fuel Rail




Example of GDI fuel rail complete assy with injector



Injector Cup



Wax pattern with gate/riser




Ceramic Shell after dewax



Counter gravity casting




Directional solidification



SSCLA sprue with a cylindrical symmetry arrangement allowing radial heat flow and solidification.



Schematic showing the directional solidification of the part.




The part design as well as the gating position and size are important for directional solidification to occur properly

The gating size is optimized and verified during the prototype process. Production would use the verified gate geometry





Solidification Modeling

Gate #1




Gate #2



Final gate design




Example of Fuel System Component Soundness




Micrography :

0.003% porosity in any 1 x 1.25 mm field of view



part

gate



Typical X-ray image



Factors controlling casting soundness

- **Metal chemistry**
 - Checked 3 times per crucible (adjusted if required) and once on castings per crucible
- **Metal temperature**
 - Controlled with immersion thermocouples in the melt
- **Mold temperature**
 - Controlled by burnout oven temperature controls and limits on the time from when the mold is removed from the oven until it is cast
- **Rate of mold filling with metal**
 - Counter gravity mold filling is controlled by a computer vacuum control system.
- **Metallurgical cleanliness**
 - Metal is drawn from the melt core under the surface and at controlled temperature
- **Controlled solidification:**
 - Amount of ceramic shell applied to the mold controlled by robot programming and shell recipe
 - Part spacing on the sprue controlled by ring die injection.
 - Gate size and placement on the casting, optimized during development



Process development for fuel system components

- **Gate optimization:**
 - Computer modeling, casting trials, Xray, and polished sections.
- **Process robustness by variation of process factors :**
 - metal temperature,
 - mold temperature
 - gate size.
- The robustness study is done to maximize the size of the green zone and to center the production operating range within the green zone.



Fuel System Component Production


Production key control items:

- Control of the process variables that control soundness
- Foundry control X-ray
 - X-ray acceptance levels are typically divided into two areas
 - Dry area (bolt area)
 - Fluid (fuel passageway) area
- X-ray levels follow ASTM E192



Example of X-Ray Inspection

1.- Part mapped in 2 areas



Fluid area

Dry area

2.- **Acceptance criteria** used for the Fluid area is tighter than the Dry area.

Standard used:

ASTM E-192 , “INVESTMENT STEEL CASTINGS FOR AEROSPACE APPLICATIONS



Example of X-Ray Inspection

3- Acceptance Criteria for X-Ray Inspection

ASTM E -192 Reference Plates for $\frac{3}{4}$ inch thickness:

Fluid Area:

Defect: Shrinkage

* Acceptance level : Dendritic Level 4 Grade “C”, it is not accepted, Filamentary or Cavity

Defect : Gas

* Acceptance level: Level 3 Grade “B”

Dry Area:

Defect : Shrinkage

* Acceptance Level: Dendritic Level 6 Grade “D” , it is not accepted, Filamentary or Cavity

Defect: Gas


* Acceptance level : 5 Grade “C”



Example of X-Ray Inspection

4.- Xray in 4 views :

- a) 5% of the Batch is evaluated in the Views 2 & 3
- b) 100% Views 1 & 4
- c) If it is found a defective piece in the 5% of the views 2& 3 the batch is 100% X-rayed in those views.





Conclusion

Hitchiner has been producing millions of castings for GDI applications, and has achieved 2ppm leakage so far.

Countergravity process combined Hitchiner expertise and experience provides the robust capability to produce reliable castings for critical applications such as fuel pressurized components, rocker arms, aerospace turbine blades.

Visit our stand in Hall 3, N° 3130,

www.hitchiner.com



Counter gravity beer: fast and clean



Enjoy a glass of counter gravity beer at our stand in Hall 3, 3130

Growing through Excellence